



HUAFENG Electronic ignitors are designed and manufactured in accordance with IEC & ANSI standards and certified by CE & CQC. The quality achieves the world advanced level. The product specification is a tandem type which can meet the demands of starting various lamps. It has high temperature resistance with $t_c = 105^\circ\text{C}$ which would allow our ignitors operate under hazardous environment.

	(V)	(A)	(W)	t_c	t_a		(kg)	Size (mm)				(mm ³)
Model	Voltage	Max current	Lamp	$^\circ\text{C}$	$^\circ\text{C}$	Hz	Weight	a	b	c	QTY/Carton	Carton Size
CD-7-P	220~240V	5	HPS/MH70-400	105	-10~50 $^\circ\text{C}$	50/60	0.2	80	35	25	30	380*280*150
CD-8-P	220~240V	15	HPS/MH400-1000	105	-10~50 $^\circ\text{C}$	50/60	0.4	95	50	35	30	380*280*150
CD-7-A	220~240V	5	HPS/MH70-400	105	-10~50 $^\circ\text{C}$	50/60	0.2	80	35	25	30	380*280*150
CD-8-A	220~240V	15	HPS/MH400-1000	105	-10~50 $^\circ\text{C}$	50/60	0.4	95	50	35	30	380*280*150