

Capacitors

Huafeng capacitors are CQC, CE certified and listed in accordance with standards IEC61049. High temperature resistance design $t_c = 105^\circ\text{C}$, built-in discharge resistor which will prevent electrical shock; it is also featured with built-in explosion-proof and temperature protection device. ROHS compliant and insulation materials are Grade VO. All of capacitors are design 10 years life time.

Model	u F Capacitor	V Voltage	ϕ mm	(mm) Length	(kg) Weight	Hull
PFC6-A	6	250V/50~60Hz	34	70	0.045	Al.
PFC8-A	8	250V/50~60Hz	34	70	0.045	Al.
PFC12-A	12	250V/50~60Hz	34	70	0.05	Al.
PFC15-A	15	250V/50~60Hz	40	80	0.055	Al.
PFC18-A	18	250V/50~60Hz	40	80	0.08	Al.
PFC25-A	25	250V/50~60Hz	40	80	0.085	Al.
PFC32-A	32	250V/50~60Hz	40	80	0.095	Al.
PFC50-A	50	250V/50~60Hz	50	90	0.16	Al.
PFC100-A	100	250V/50~60Hz	50	90	0.21	Al.
PFC6-P	6	250V/50~60Hz	34	70	0.045	Plastic
PFC8-P	8	250V/50~60Hz	34	70	0.045	Plastic
PFC12-P	12	250V/50~60Hz	34	70	0.05	Plastic
PFC15-P	15	250V/50~60Hz	40	80	0.055	Plastic
PFC18-P	18	250V/50~60Hz	40	80	0.08	Plastic
PFC25-P	25	250V/50~60Hz	40	80	0.085	Plastic
PFC32-P	32	250V/50~60Hz	40	80	0.095	Plastic
PFC50-P	50	250V/50~60Hz	50	90	0.16	Plastic
PFC100-P	100	250V/50~60Hz	50	90	0.21	Plastic

